







#### 7] Draft (static) Dead Rise Draft (plane) Draft (static) Beam THE RIVERINE SHALLOW DRAFT VESSEL (RSDV-28) THE RIVERINE SHALLOW DRAFT VESSEL (RSDV-24) Fuel Capacity Displacement Draft (plane) Length Length (w/Ops Deck) THE RIVERINE SHALLOW DRAFT VESSEL (RSDV-28) Fuel Capacity Displacement Dead Rise Draft (static) Draft (plane) Beam Length (w/Ops Deck) Fuel Capacity Displacement Dead Rise Length (w/Ops Deck) THE RIVERINE SHALLOW DRAFT VESSEL (RSDV-21) Fuel Capacity Displacement Dead Rise Draft (static) Draft (plane) Length (w/Ops Deck) THE RIVERINE SHALLOW DRAFT VESSEL (RSDV-18) 24'-0" 26-8" 9'-8" 28'-0" 31'-2" 11'-4" 8" 6,950 lbs 120+ gallons 28'-0" 31'-2" 11'-4" 21'-0" 23'-4" 8'-4" 3,900 lbs 55+ gallons 4,900 lbs 18'-0" 19'-6" 100+ gallons 5° 10′ 30+ gallons 1,600 lbs 8.5m 9.5m 3,152 kg 3.45m 8.5m 2,223 kg 379+ litres 7.3m 8.1m 1,769 kg 265+ litres 28cm 5° 6.4m 7.1m 726 kg 113+ litres 5.5m 5.9m 454+ litres 20cm 30cm 9.5m 2.54m 38cm 2.9m 10cm 2.4m 25cm 15cm 10cm

Beam Draft (plane) Draft (static)

Length (w/Ops Deck)

3.45m

18cm

Dead Rise Displacement

Fuel Capacity

7,600 lbs 3,152 kg 120+ gallons 454+ litres









SHALLOW WATER



WEEDS & DEBRIS




PAYLOAD



## THE RIVERINE SHALLOW DRAFT VESSEL (RSDV-24)

The Riverine Shallow Draft Vessel (RSDV-24) is the workhorse of the ReconCraft fleet. With a large payload for crew and equipment along with a patrol range over 250 NM, the RSDV-24 is well suited for extended operations in narrow and debris-filled waterways where little infrastructure or support is available. Powered by a 370 HP diesel L and the Hamilton HJ 241 Water Jet, the RSDV can reach speeds over 45 MPH in as little as 6" of water. Alternative diesel or gasoline propulsion systems are available.

# **RSDV-24CC General Dimensions**



All specifications and measurements are approximate and subject to change without notice. Performance data is not guaranteed and can vary depending upon cargo/fuel load, owner's equipment, temperature, sea-state, and other variables.

## **RSDV-24CC Advantages**



# **Components & Specifications**

### **Specifications**

Length	24'-0"	7.3m
Length (w/Ops Deck)	26'-8"	8.1m
Beam	9'-8"	2.9m
Draft (plane)	6"	15cm
Draft (static)	12"	30cm
Dead Rise	6°	6°
Displacement	4,900 lbs	2,223 kg
Fuel Capacity	100+ gallons	379+ litres

### **Propulsion**

Engine	Yanmar 6LYA-STP 370 HP Turbo Diesel	
Optional Marine Gear	ZF, Borg Warner, or Twin Disc	
Jet	Hamilton HJ 241 Water Jet	

Alternative propulsion configurations available based on specific needs.

### **Performance**

Max Speed	45+ MPH	72+ KPH
Cruise Speed	25-35 MPH	40-56 KPH
Range	250+ NM	402+ Km

#### Qualities

- Efficient, powerful, and durable propulsion systems capable of operating in vegetation, debris, and shallow water result in outstanding patrol coverage.
- Ergonomic designs, created with input from actual operators, significantly reduce crew fatigue and maintain crew safety.
- Simplistic and redundant mechanical and electrical systems, with reserve capacity to support upgrades, yield unparalleled detection, monitoring, and interdiction capabilities.
- Rugged hull structure, commonality of parts, and full access to the hull via removable deck plates significantly decrease maintenance time and ownership costs.
- Multi-mission configurations result in tremendous tactical capability.

### **Configuration**

The center console arrangement is specifically designed to minimize crew fatigue during long patrols while giving the pilot and co-pilot easy access to all controls. The bench seat is capable of moving fore/aft and up/down depending on the operators' preferences. The console and overhead areas can be configured with various seating and storage options.

# **Features & Options**

#### **Console**

- Forward Angled Windows to Reduce Glare\*
- Shock Mitigating Seats w/ Ballistic Nylon
- LED Red/White Lighting
- Mini Hard Top
- Extended Hard Top

### **Hull Protection & Fendering**

- 5086 Alloy Hull\* Up to 0.250" Bottom Plating
- Proprietary CrashCoat™ Hull Protection System
- UHMW Slider Keel Pad (22")
- Black or Non-Marking Rub Rail
- High Density Foam Collar / Sponson

## **Mechanical/Electrical Systems**

- RACOR Fuel Filtration System
- Raw Water Cooling System\*
- 12V DC Distribution System\*
- Multiple DC Battery Banks\*

#### Deck

- Large Swim/Operations Deck\*
- Tactically Designed Walk Around Configuration\*
- Full Deck Lighting Package (Flood & Spreader)
- Flush Mount Flat Top Cleat Package
- 4-Point Lifting Eyes
- Tow Bollard and Reel
- Anchor Locker
- Marine Grade Paint Coating System
- 3M Safety Walk™ Deck Tread
- Battery Charger & Monitor
- Engine Compartment Sound Insulation
- Tie Points 8x Floor Mounted
- 12V Accessory Plugs
- Long Gun Storage System

 Patent Pending Weed-Debris Grate w/Helm Lever or Actuator

## **Safety**

- Foam Collar Flotation
- (2) Bilge Pumps (Auto and Manual)\*
- Fire Extinguisher\*
- Anti-Fatigue Deck Matting

## **Additional Options**

- Whelen LE Lighting/Loudhailer Package
- Side Scan Sonar
- Fire-Fighting System w/ Remote Operated Nozzle
- Forward Looking Infrared (FLIR) Camera
- AIS System
- Weapon Mount Foundations (ITAR Dependent)
- Ballistic Protection (ITAR Dependent)
- Side Dive Doors
- AC Electrical Inverter
- Heated Windshield Glass
- Rescue Basket Mounts (Quick-Release)
- HC-130 Deployment Kit
- Many other mission specific items. Call for details.

# **Additional Information**

For more information about this product, or any of ReconCraft's products, please contact us directly or visit our website:

Phone: +1 (877) 645-7761

Email: info@reconcraft.com

Web: reconcraft.com

\*Indicates standard features on base model.

**Weed & Debris (Flood Zone) Operations**